

## Pièces de jonction A/F

### Unibride libre FONTE

DN 50 au DN 600  
PFA 16 bar  
pour tubes fonte ductile



Pour DN 500 et 600  
ISO PN 16 : utiliser série 260

### Adaptateur PVC PRESTOPLAST

PFA 16 bar  
Joint fourni



### Manchon PVC GIBAULAST

PFA 16 bar



DN bride mm	Ø mm	ISO PN	Poids Kg
50	66	10/16	2,0
60	77	10/16	2,0
80	98	10/16	3,8
100	118	10/16	4,0
125	144	10/16	4,2
150	170	10/16	6,6
200	222	10	11,1
200	222	16	8,7
250	274	10	15,8
250	274	16	17,6
300	326	10	21,5
300	326	16	21,7
400	428	10	44,1
400	428	16	46
500	532	10	60,0
600	636	10	84,7

DN bride mm	Ø mm	ISO PN	Poids Kg
40	40	10/16	2,85
40	50	10/16	3,13
50/60/65	63	10/16	3,6
60/65	75	10/16	3,9
80	90	10/16	4,5
100	110	10/16	5,1
125	125	10/16	6,8
125	140	10/16	7,5
150	160	10/16	7,94
200	200	10	12,3
200	225	10	15
250	250	10	23,5
250	280	10	23
300	315	10	25

DN bride mm	Ø mm	ISO PN	Poids Kg
40			2,66
50			2,1
63			2,5
75			3,67
90			3,3
110			4
125			7,3
140			7,3
160			8
200			12,09
225			16,05
250			29
280			25
315			30,23