

TABLEAU DE REPÉRAGE DU DIAMÈTRE EXTÉRIEUR DES CONDUITES D'EAU POTABLE

DN tube mm	PVC	PE(3)	Fonte Ductile	Fonte Grise	Acier	Fibre Ciment (2)
40	40	40	57	54	45	
				60	48	
50	50	50	66	70	54	
				74	57	
					60	
60	63	63	77	84	70	85 (a)
	75	75			73	89 (b)
65					75	
					76	
					83	
80	90	90	98	104	89	106 (a)
						109 (b)
100	110	110	118	125	108	131 (a)
				135	114	133 (b)
					127	
125	125	125	144	152	133	163 (a)
	140	140		165	140	166 (b)
					141	
150	160	160	170	178	159	194 (a)
		180		190	165	200 (b)
					168	
					178	
175			196	201	194	227-228
200	200	200	222	229	219	249 (a)
		225		240		254 (b)
	222 (1)	222 (1)	248	259	245	
	225	225				
250	250	250	274	281	273	309/314 (a)
	274 (1)	280		286	299	314 (b)
300	315	315	326	331	324	371 (a)
	326 (1)					376 (b)
350			378		356	
					368	
375				426		
400	400		428	453	419	436/446
450			480		457	498/532
500	500		532		506	
600	630		636		609	
800			841		813	869
						915
900			943		914	970
						1024

(1) PVC Biorienté PN25

(2) Diamètre extérieur du tuyau et non celui de la partie ouverte

(3) PE 100 SDR 11 PN16

(a) cl 20/25

(b) cl 30